

VULCANO SERIES

LFS 60 P



Series of safes certified according to European standard LFS 60P EN15659 for fire resistance. Designed to protect documents, since the temperature increase inside the safe at 60 minutes is less than 170°, which guarantees the integrity of the paper, which decomposes from 177°C. Also ideal for storing valuable belongings that must be protected from theft.



Interior drawer situation:
 · 75-E model: upper part.
 · 120-E and 140-E: lower part.



Features

- Door thickness:** 32-E / 51-E / 75-E models 96 mm.
120-E model 117 mm.
140-E model 96 mm.
- Wall thickness:** 32-E model 51 mm.
51-E model 52 mm.
75-E model 69 mm.
120-E model 82 mm.
140-E model 70 mm.
- Interior complete with fire-proof concrete.
- Bolts:** 32-E / 51-E models 2 x Ø15 mm.
75-E model 3 x Ø25 mm.
120-E / 140-E models 6 x Ø25 mm.
- Colour:** Grey (RAL 7035)
- Interior drawer** in 75-E, 120-E and 140-E models.
- Anchor holes:** 1 floor.

Locking system

- Lock and keyboard:**
32-E and 51-E models:
Digital keyboard + knob.

75-E, 120-E and 140-E models:
High security lock + digital keyboard+ knob.
- User code plus emergency code with variable length, 4 to 6 digits.
- Power supply :** 4 AAA (1,5V) batteries.
Located in the exterior. Easy to replace.



MOD.	COD		mm.	(H x W x D)		kg	L.	Cod. EAN 8421461
32-E	10510	EXTERIOR	315 x 445 x 425	INTERIOR 212 x 341 x 296	1	38	21	105103
51-E	10511	EXTERIOR	510 x 445 x 425	INTERIOR 407 x 341 x 296	1	51	41	105110
75-E	10512	EXTERIOR	790 x 485 x 450	INTERIOR 607 x 346 x 301	1	109	64/8	105127
120-E	10513	EXTERIOR	1255 x 711 x 580	INTERIOR 1034 x 546 x 418	2	311	236/26	105134
140-E	10516	EXTERIOR	1391 x 711 x 580	INTERIOR 1170 x 546 x 418	2	332	267/26	105165